

Advances in AI-Enabled Predictive Maintenance: Models, Industrial Applications, and Research Frontiers

Prafull V. Dhole¹, Ankit Manderna¹, Shraddha Wangujare¹
 Department of Artificial Intelligence, NIELIT, Aurangabad, India, 431004
 dholepv.111@gmail.com

Abstract. Predictive Maintenance (PdM), a paradigm enabled by the integration of Artificial Intelligence (AI), the Industrial Internet of Things (IIoT), and advanced data analytics, is presently navigating a crucial shift in the industrial landscape from reactive to preventative maintenance tactics. This change makes it easier to switch from fail-and-fix approaches to predict-and-prevent tactics, which maximizes asset availability, lowers operating costs, and improves safety. With a thorough technical examination of deep learning architectures such as Convolutional Neural Networks (CNNs), Long Short-Term Memory (LSTM) networks, Autoencoders, and the new Transformer models, this paper investigates the state-of-the-art in AI-enabled PdM. With particular focus on energy systems, thermal power generation, and rotating machinery—areas where thermodynamic efficiency and energy analysis are crucial—it critically investigates the implementation of these models across important sectors. Additionally, the study addresses ongoing issues with data scarcity, model interpretability, and cybersecurity in safety-critical situations by identifying and discussing emerging research horizons including Explainable AI (XAI), Digital Twins, and Physics-Informed Machine Learning (PIML).

Keywords: Predictive Maintenance, Artificial Intelligence, Deep Learning, Industrial IIoT, Condition Monitoring.

(Article history: Selected papers from NIELIT's International Conference on Communication, Electronics and Digital Technologies (NICE-DT'26), 29-30 Jan, 2026, Gorakhpur, India)

1 Introduction

Economic sustainability and operational safety are fundamentally determined by the dependability and efficiency of contemporary industrial systems, from intricate thermal power plants to highly precise automated production lines. Throughout history, the management of these tangible assets has changed across several generations, each characterized by the technological advancements of its time.

The foundation of the first generation, Reactive Maintenance (sometimes called Run-to-Failure), is the idea that assets should only be repaired in the event of a functional failure. Although this approach reduces initial planning and condition monitoring expenses, it always results in catastrophic unplanned downtime, possible secondary damage to linked systems, and serious worker safety risks. This method's volatility makes it inappropriate for vital infrastructure [1].

Regardless of the machine's actual condition, the second generation, Preventive Maintenance (Time-Based), aims to reduce these risks by planning repairs and replacements at certain intervals. This method is intrinsically wasteful even though it increases reliability when compared to reactive solutions. It often leads to the early removal of parts with substantial Remaining Useful Life (RUL), which drives up maintenance expenses and resource usage. According to studies, conservative scheduling rather than real asset degradation may be the cause of up to 30% of needless preventive maintenance procedures [2].

The third and most sophisticated generation, Predictive Maintenance (PdM), allows for a Just-in-Time maintenance approach. PdM uses real-time condition monitoring to forecast an asset's future state and only plans actions when empirical data points to an imminent failure. The P-F curve, which shows the time gap between the identification of a potential failure (P) and the functional failure (F), serves as the theoretical foundation for this approach. AI-driven PdM's main goal is to maximize this P-F interval by identifying minute irregularities long before they become audible noise, vibration, or thermal runaway, such as micro-structural fatigue in bearings or entropy generation spikes in heat exchangers [3].

High-dimensional, high-frequency time-series data streams have been made possible by the widespread deployment of sensing technology made possible by Industry 4.0. These streams usually comprise mass flow rates, temperatures, pressures, vibration signatures, and sound emissions for mechanical and energy systems. However, conventional statistical analysis is inadequate due to the sheer amount, velocity, and variety of this data. The computational engine required to process this raw data, learn intricate non-linear representations of degradation, and produce useful prognostics is provided

by artificial intelligence (AI), and in particular, deep learning (DL) [4], [5].

Although numerous studies have reviewed AI-based predictive maintenance, most existing works focus primarily on algorithmic performance or generic rotating machinery applications, with limited consideration of the underlying physical degradation mechanisms. This review distinguishes itself by presenting a physics-aware perspective on AI-enabled predictive maintenance, with particular emphasis on energy systems, thermal power plants, and large-scale industrial assets, where thermodynamic efficiency and exergy destruction are critical indicators of system health.

1.1 Review Methodology

This review is based on a structured survey of peer-reviewed literature obtained from IEEE Xplore, Scopus, ScienceDirect, and SpringerLink, primarily covering publications from 2010 to 2025. Keywords related to AI-enabled predictive maintenance, deep learning, industrial IoT, and condition monitoring were used. The selected studies were screened for industrial relevance, technical rigor, and applicability to energy systems and rotating machinery, and subsequently organized according to sensing technologies, AI architectures, application domains, and emerging research trends.

2 The Predictive Maintenance Data Pipeline

A strong cyber-physical architecture that can connect the digital abstraction of cloud computing with the physical reality of the plant floor is necessary for implementing AI for PdM; it is not only a software exercise. Any PdM system's foundation is the data pipeline, which includes data collection, transport, processing, and analysis.

2.1 Sensor Technology and Data Acquisition

The fidelity of any predictive model is intrinsically limited by the physics of the sensing layer.

Vibration Sensors (Accelerometers): These are the industry standard for keeping an eye on machinery that rotates. Piezoelectric accelerometers record high-frequency oscillations (often up to 20 kHz), which are a sign of unbalance, shaft misalignment, gear meshed problems, and bearing issues [6].

Thermal Imaging and Thermography: Temperature is a leading indicator of efficiency loss but a trailing indicator of failure. Thermal anomalies in electrical transformers are a sign of insulation failure. Accurate temperature measurements are essential for determining heat transfer coefficients and detecting heat exchanger fouling in thermodynamic systems. Non-invasive monitoring of these temperature profiles is made possible by infrared thermography [7].

Acoustic Emission (AE): High-frequency stress waves, such as those caused by friction or crack propagation, are detected by AE sensors when strain energy is released. In slow-rotating bearings with little vibration energy, AE is very useful for identifying early-stage problems [8].

Process Parameters: SCADA systems gather information on flow rates, pressures, voltage, and current in the production of energy. Calculating system-level metrics like thermal efficiency and exergy destruction rates need these factors.

2.2 Signal Processing and Feature Engineering

Due to signal noise, variable sampling rates, and large dimensionality, raw sensor data is rarely appropriate for direct consumption by AI models. Significant features that are associated with machine health are extracted using signal processing techniques.

Time-Domain Analysis: Calculations are made for statistical parameters such as Crest Factor, Kurtosis, Skewness, and Root Mean Square (RMS). For example, even when the total energy (RMS) stays constant, kurtosis is extremely sensitive to impulsive errors (such as a ball bearing hitting a pit during a race).

Frequency-Domain Analysis: Time-series signals are transformed into the frequency domain using the Fast Fourier Transform (FFT). This makes it possible to identify particular fault frequencies connected to different mechanical components, such as gear mesh frequency and ball pass frequency [9].

Time-Frequency Analysis: Techniques like the Short-Time Fourier Transform (STFT) and Wavelet Transform (WT) are crucial for non-stationary signals, which are common in variable speed machinery like wind turbines. The model can examine frequency components as they change over time using the Wavelet Transform, giving a multi-resolution picture of the signal [10].

3 AI Models and Architectures

For smaller, structured datasets, conventional Machine Learning (ML) techniques like Random Forest (RF), Support Vector Machines (SVM), and k-Nearest Neighbors (k-NN) are still useful, but human feature engineering requires a high level of domain expertise. Deep Learning (DL) has emerged as the optimum approach for high-frequency, complicated industrial data because it automates feature extraction, learning hierarchical representations directly from raw signals [11].

3.1 Convolutional Neural Networks (CNN)

Originally designed for computer vision, CNNs have been adapted with great success for vibration analysis.

Architecture & Mechanism: Convolutional kernels in a 1D-CNN are used to extract local characteristics like peaks and impulses by sliding across the raw time-series signal. The 1D signal is first transformed into a visual representation (such as a spectrogram or continuous wavelet transform) in a 2D-CNN method. Next, the network identifies spatial patterns in these pictures that match fault signatures.

Applications: CNNs are particularly good at fault diagnosis, which involves identifying the particular kind of problem (e.g., differentiating between an outer race defect and an inner race bearing flaw). They can learn to discard unimportant signal components and are resilient to background noise [12].

3.2 Recurrent Neural Networks (RNN) and LSTM

Conventional feedforward networks make the assumption that inputs are unrelated to each other. For time-series data, where a machine's present state is highly dependent on its past states, this assumption is false.

Architecture & Mechanism: RNNs have a memory loop to deal with this. Nevertheless, the vanishing gradient problem hinders typical RNNs' capacity to learn long-term dependencies. This is addressed with Long Short-Term Memory (LSTM) networks, which use an advanced gating system (input, forget, and output gates) to control information flow and preserve pertinent historical data over lengthy sequences.

Applications: When it comes to prognostics, particularly when evaluating the Remaining Useful Life (RUL), LSTMs are the gold standard. LSTMs may monitor the progressive deterioration route of a component (such as battery capacity fade, turbine blade erosion, or filter clogging) across hundreds of operational cycles by examining lengthy sequences of operational data [13]. Recent developments include hybrid architectures that achieve better outcomes in complicated situations by combining CNNs for feature extraction with LSTMs for temporal reasoning [14].

3.3 Autoencoders for Anomaly Detection

Failure data is rare or nonexistent in many industrial contexts, whereas normal operation data is plentiful. Supervised learning is challenging because of this imbalance.

Architecture & Mechanism: An unsupervised neural network that has been trained to compress (encode) input data into a lower-dimensional latent space and then reconstruct (decode) it back to the original input is known as an autoencoder. Only healthy data are used to train the model.

Applications: The model will not correctly recreate the input during the deployment phase if it comes across aberrant data, such as a machine vibrating in a way it has never seen before. An anomaly score is a high re-construction mistake. This method is perfect for finding new, undiscovered failure modes without the need for labeled fault data [15].

3.4 Transformers and Attention Mechanisms

The Transformer architecture, which has revolutionized Natural Language Processing (NLP), is rapidly entering the PdM domain. Table 1 shows the comparison of AI architectures for predictive maintenance.

Architecture & Mechanism: Transformers use Self-Attention methods to simultaneously evaluate the relative value of several time steps, in contrast to RNNs that process data sequentially. This makes it possible to process data in parallel and identify incredibly long-range connections in complicated datasets.

Applications: When it comes to predicting complex system behaviors, like grid load prediction or multi-variate process control in chemical plants, where the interaction between variables (like the lag between a temperature spike at the inlet and a pressure drop at the outlet) is dynamic and complex, transformers are proving to be superior [16].

Table 1: Comparative Analysis of AI Architectures for PdM

Model Architecture	Learning Paradigm	Key Strengths	Limitations	Optimal Use Case
--------------------	-------------------	---------------	-------------	------------------

RandomForest	Supervised (Ensemble)	Highly interpretable (feature importance), handles tabular data robustly.	Performs poorly on raw signals; requires manual feature extraction.	Root cause analysis using structured SCADA logs.
CNN	Supervised (Deep)	Powerful automated feature extraction from raw signals or spectrograms.	Ignores temporal order; requires large, balanced datasets.	Bearing and gear fault diagnosis via vibration analysis.
LSTM/GRU	Supervised (Recurrent)	Captures long-term temporal trends and degradation paths.	Computationally expensive to train; sequential processing limits speed.	RUL estimation of batteries, turbines, and engines.
Autoencoders	Unsupervised	Effective anomaly detection without labeled fault data.	Defining the error threshold is complex; does not classify fault type.	Monitoring stable processes for unseen anomalies.
Transformers	Self-Attention	Handles very long sequences; global context awareness; parallelizable.	Extremely data-hungry; high memory footprint during inference.	Complex, multi-variable forecasting (e.g., power grid load).

4 Industrial Applications

The application of AI-enabled PdM varies significantly across industries, dictated by the criticality of assets and the physics of the failure modes. A typical workflow of AI-driven predictive maintenance is shown in Fig. 1, whereas the mind map of the processes involved in the predictive maintenance is shown in Fig. 2.

4.1 Energy Systems and Power Generation

In the energy sector, reliability is of greatest concern. Unplanned downtime not only results in revenue loss but can also destabilize the grid.

Wind Turbines: These days, wind turbines are intricate electromechanical devices with hundreds of sensors. To forecast breakdowns in crucial parts like the gearbox, main bearing, and generator, artificial intelligence algorithms examine SCADA data (wind speed, pitch angle, rotor speed, power output). In order to eliminate false positives brought on by wind gusts, ensemble learning techniques are frequently utilized to connect exterior weather conditions with interior mechanical stress [17].

Power Transformers: Grid stability depends on the condition of power transformers. The main diagnostic technique is Dissolved Gas Analysis (DGA). The ratios of dissolved gases (hydrogen, methane, ethylene, and acetylene) in the insulating oil are analyzed by AI models, especially Hybrid CNN-LSTM architectures, to predict faults like arcing, overheating, and partial discharge with much higher accuracy than conventional ratio methods (e.g., Rogers ratio or IEC ratios) [18].

Thermal Power Plants & Exergy Analysis: AI is progressing beyond basic mechanical vibration monitoring in thermal power generation. AI models are used to track the Exergy Destruction Rate in parts like boilers, condensers, and feed water heaters by incorporating thermodynamic concepts. The baseline energy efficiency profile of a heat exchanger under different load scenarios can be learned by an LSTM model. Long before gross thermal performance declines noticeably, deviations from this established baseline may be an indication of fouling, tube leakage, or incorrect combustion tuning. This innovative method of improving plant efficiency combines Deep Learning with Second Law thermodynamics [19], [20].

4.2 Manufacturing and Rotating Machinery

CNC Machining: One traditional PdM use is tool wear prediction. The spindle current and acoustic mission characteristic gradually alter as a cutting tool dulls. These inputs are used by AI models to forecast when a tool should be changed (just-in-time replacement), saving workpiece damage and reducing scrap rates [21].

Pump and Motors: Pumps are essential tools in water treatment and chemical processing. In order to identify certain flaws like cavitation, misalignment, and bearing wear, edge-deployed AI models analyze vibration data locally. By lowering the latency and bandwidth cost of sending high-frequency vibration data to the cloud, Edge AI allows for real-time protection [22].




Fig.1.AI-EnabledPredictiveMaintenanceWorkflow



Fig.2.Mindmapofthepredictive maintenance



5 Research Frontiers and Emerging Trends

As the field matures, research is shifting from applying standard algorithms to addressing the unique challenges of industrial environments.

5.1 Digital Twins (DT) and Physics-Informed ML

The integration of AI with Digital Twins represents the zenith of PdM. A Digital Twin is a dynamic, physics-based simulation synchronized with the real asset via real-time data [23].

Physics-Informed Machine Learning (PIML): When extrapolating outside their training data, pure data-driven models frequently break physics rules (such as the conservation of mass or energy). In order to solve this, digital twins create artificial data using physical laws (such as computational fluid dynamics or finite element analysis). AI models are trained on failure scenarios that have seldom or never happened in the actual world using this synthetic data. Engineers can forecast factors like the core temperature of a turbine blade that cannot be directly detected thanks to this virtual sensing capacity [24], [25].

5.2 Explainable AI (XAI)

The black-box aspect of neural networks is a major obstacle to Deep Learning's adoption in safety-critical industries (like nuclear power or aircraft). Before approving expensive downtime, engineers and operators must comprehend why a model anticipates a failure [26].

Techniques: Local interpretability is offered by XAI techniques like LIME and SHAP (SHapley Additive exPlanations). Grad-CAM (Gradient-weighted Class Activation Mapping), for instance, can pinpoint the precise area of the vibrations spectrogram that a CNN used to anticipate a bearing defect. This promotes a person-in-the-loop strategy by fostering trust between the AI system and the human expert [27].

5.3 Generative AI for Data Augmentation

Industrial datasets are infamously unbalanced; failure data is incredibly rare because equipment operates normally 99% of the time. Poor sensitivity is usually the result of training a classifier on such skewed data.

Generative Adversarial Networks (GANs): GANs are being used by researchers to produce realistic fake defect data. A discriminator network tries to separate the artificial fault signatures produced by a generator network from actual data. High-fidelity synthetic data is produced by this adversarial process, which may be used to balance datasets and train more resilient PdM models without waiting for real failures to happen [28], [29].

6 Challenges and Barriers to Implementation

Despite the proven capabilities of AI in controlled environments, scaling Predictive Maintenance solutions in diverse industrial settings presents significant hurdles.

6.1 Data Quality and The Dirty Data Problem

The most common problem in industrial AI is data-centric rather than computational. Industrial settings are noisy by nature; sensor readings can be distorted by electro-magnetic interference; and human logs, such as maintenance records, are sometimes inaccurate or lacking. Additionally, class imbalance is a serious problem. Catastrophic failures are uncommon in well-maintained plants, but models need examples of failures to learn properly. Due to this paucity, costly data augmentation methods or unsupervised anomaly detection which has a high false-positive rate are required [30].

6.2 The Domain Shift and Generalization Gap

When applied to an identical pump (Pump B) running under slightly different environmental circumstances or load profiles, a model trained on a particular pump (e.g., Pump A) frequently fails. The copy-paste

scalability of AI systems is hindered by this phenomenon, called Domain Shift. Although effective solutions for highly non-linear mechanical systems are still elusive, strategies like Transfer Learning and Domain Adaptation are current research fields that try to enable models to generalize across diverse assets without requiring retraining from scratch [31].

6.3 IT-OT Convergence and Interoperability

Information technology (IT) and operational technology (OT) must converge in order to implement PdM. Different, proprietary protocols (such as Modbus, Profibus, and CAN bus) that were not intended for high-bandwidth data transfer to the cloud are frequently used by legacy industrial assets to interact. It takes a lot of money to retro-fit these brownfield sites with contemporary IIoT gateways that support MQTT or OPC-UA. Furthermore, feature engineering and model validation depend on bridging the technical and cultural divide between reliability engineers (OT) and data scientists (IT) [22].

6.4 Computational Cost and Edge Constraints

Transformers and deep LSTMs in particular are computationally costly deep learning models. Due to bandwidth and storage costs, sending terabytes of unprocessed vibration data to the cloud for processing is frequently too expensive. Although edge computing provides a solution by processing data locally, the processing power and memory of edge devices, such as industrial gateways based on Raspberry Pis, are constrained. A crucial technical difficulty is optimizing sophisticated neural networks to operate on limited hardware (via quantization or pruning) without compromising accuracy.

6.5 Cybersecurity Risks

The attack surface for cyber threats is increased when vital physical infrastructure, such as chemical reactors or power plant turbines, is connected to networked PdM systems. Physical harm or safety problems could result from using a compromised PdM system to conceal real alarms or cause false shutdowns. Just as important as guaranteeing the prediction accuracy of AI-driven maintenance systems is assuring their cybersecurity [32].

7 Conclusion

In the era of Industry 4.0, AI-driven predictive maintenance has evolved from a theoretical possibility to a competitive requirement. The transformation from reactive firefighting to proactive asset management is made possible by the confluence of domain-specific knowledge (Thermodynamics, Vibration Analysis) with Deep Learning architectures (CNN, LSTM, Transformers).

The future of PdM is in Hybrid Systems, even though Deep Learning outperforms conventional techniques in feature extraction and pattern recognition. These technologies will integrate the physical interpretability of digital twins and thermodynamic models with the data-driven power of artificial intelligence. By limiting predictions to physical rules, this method not only increases accuracy but also builds trust through Explainable AI.

It will take interdisciplinary cooperation between mechanical engineers, data scientists, and plant operators to address the remaining issues, including data quality, interoperability, and the IT-OT gap. AI-enabled PdM will be the foundation of robust, energy-efficient, and autonomous industrial systems if these obstacles are removed.



References

1. Mobley, R. K.: *An Introduction to Predictive Maintenance*. Elsevier (2002).
2. Swanson, L.: Linking maintenance strategies to performance. *International Journal of Production Economics* 70(3), 237-244 (2001).
3. Patel P., Patel, R.: AI-Driven Predictive Maintenance in Manufacturing: A Multi-Component System Approach. *Research Annals of Industrial and Systems Engineering* 2(1) (2025).
4. Lee, J., Kao, H. A., Yang, S.: Service innovation and smart analytics for Industry 4.0 and big data environment. *Procedia CIRP* 16, 3-8 (2014).
5. Zhao, R., Yan, R., Chen, Z., Mao, K., Wang, P., Gao, R. X.: Deep learning and its applications to machine health monitoring. *Mechanical Systems and Signal Processing* 115, 213-237 (2019). <https://doi.org/10.1016/j.ymssp.2018.05.050>
6. Zhang, S., Zhang, S., Wang, B., Habetler, T. G.: Deep learning algorithms for bearing fault diagnostics—A comprehensive review. *IEEE Access* 8, 29857-29881 (2020). doi: 10.1109/ACCESS.2020.2972859.
7. Elmessery, W. M., Habib, A., Shams, M. Y., Abd El-Hafeez, T., El-Messery, T. M., Elsayed, S., Elwakeel, A. E.: Deep regression analysis for enhanced thermal control in photovoltaic energy systems. *Scientific Reports* 14(1), 30600 (2024). <https://doi.org/10.1038/s41598-024-81101-x>
8. Mba A. G., Rao, R. H.: Acoustic emission monitoring of rotating machinery. *Shock and Vibration Digest* 38(1), 3-16 (2006).
9. Han, T., Jiang, D., Zhang, X.: Intelligent diagnosis method for rotating machinery using dictionary learning and singular value decomposition. *Sensors* 17(4), 689 (2017).
10. Feng, Z., Liang, M., Chu, F.: Recent advances in time-frequency analysis methods for machinery fault diagnosis: A review with application examples. *Mechanical Systems and Signal Processing* 38(1), 165-205 (2013). <https://doi.org/10.1016/j.ymssp.2013.01.017>
11. Zhang, L., Xu, B.: Deep Learning for Predictive Maintenance in Industrial Applications. *Journal of Industrial Technology* 38(4), 334-342 (2022).
12. Janssens, O., Slavkovikj, V., Vervisch, B., Stockman, K., Loccufier, M., Verstockt, S., van de Walle, R., Van Hoecke, S.: Convolutional neural network based fault detection for rotating machinery. *Journal of Sound and Vibration* 377, 331-345 (2016). <https://doi.org/10.1016/j.jsv.2016.05.027>
13. Zhou, Y., Li, J., Tan, W.: Predictive Maintenance Systems in Manufacturing: A Review of Machine Learning Approaches. *Journal of Manufacturing Science and Engineering* 45(6), 241-253, (2023).
14. Mateus, B. C., Mendes, M., Farinha, J. T., Martins, A.: Hybrid Deep Learning for Predictive Maintenance: LSTM, GRU, CNN, and Dense Models Applied to Transformer Failure Forecasting. *Energies* 18(21), 5634, (2025).
15. Sakurada M., Yairi, T.: Anomaly detection using autoencoders with nonlinear dimensionality reduction. in *Proceedings of the MLSDA 2014 2nd Workshop on Machine Learning for Sensory Data Analysis*, pp. 4-11 (2014).
16. Wu, N., Green, B., Ben, X., O'Banion, S.: Deep transformer models for time series forecasting: The influenza prevalence case. *arXiv preprint arXiv:2001.08317*.
17. A. Stetco et al., "Machine learning methods for wind turbine condition monitoring: A review," *Renewable Energy*, vol. 133, pp. 620-635, 2019. (2020)
18. Souahlia, T., Bounif, A., Daoud, K.: Power transformer fault diagnosis based on dissolved gas analysis using machine learning techniques. *Electric Power Systems Research* 200, 107472 (2021).
19. Dincer I., Rosen, M. A.: *Exergy: Energy, Environment and Sustainable Development*. Elsevier, (2012).
20. Sandu, G., Varganova, O., Samii, B.: Managing physical assets: A systematic review and a sustainable perspective. *International Journal of Production Research* 61, 6652-6674 (2023).
21. Teti, R., Jemielniak, K., O'Donnell, G., Dornfeld, D.: Advanced monitoring of machining operations. *CIRP annals* 59(2), 717-739 (2010).
22. Nuruzzaman, M., Limon, G. Q., Chowdhury, A. R., Khan, M. M.: Predictive Maintenance In Power Transformers: A Systematic Review Of AI And IOT Applications. *ASRC Procedia: Global Perspectives in Science and Scholarship* 1(01), 34-47 (2025).
23. van Dinter, R., Tekinerdogan, B., Catal, C.: Architecting Digital Twin-based predictive maintenance systems. *Information and Software Technology* 151, 107008, (2022).
24. Raissi, M., Perdikaris, P., Karniadakis, G. E.: Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational Physics* 378, 686-707, (2019).
25. Majumdar, R., Jadhav, V., Deodhar, A., Karande, S., Vig, L., Runkana, V.: HxPINN: A hypernetwork-based physics-informed neural network for real-time monitoring of an industrial heat exchanger. *Numerical Heat Transfer, Part B: Fundamentals* 86(6), 1910-1931 (2025).
26. Arrieta, A. B., Díaz-Rodríguez, N., Del Ser, J., Bennetot, A., Tabik, S., Barbado, A., ... Herrera, F.: Explainable Artificial Intelligence (XAI): Concepts, taxonomies, opportunities and challenges toward responsible AI. *Information fusion* 58, 82-115 (2020).
27. Wang Y., Huang, J.: Interpretable Anomaly Detection for Industrial Equipment based on Attention Mechanism. *Journal of Manufacturing Systems* 72, 101-115, (2024).
28. Mikołajewska, E., Mikołajewski, D., Mikołajczyk, T., Paczkowski, T.: Generative AI in AI-based digital twins for fault diagnosis for predictive maintenance in Industry 4.0/5.0. *Applied Sciences* 15(6), 3166 (2025).
29. Goodfellow, I. J., Pouget-Abadie, J., Mirza, M., Xu, B., Warde-Farley, D., Ozair, S., ... Bengio, Y.: Generative adversarial nets. *Advances in neural information processing systems* 27 (2014).
30. Dai, T., Zhao, Y., Yu, Y.: Generative and Predictive AI for Digital Twin Systems in Manufacturing. *Frontiers in Artificial Intelligence* 8, 2025.
31. Pan S. J., Yang, Q.: A survey on transfer learning. *IEEE Transactions on Knowledge and Data Engineering* 22(10), 1345-1359 (2010).
32. Singh R., Kaur, P.: Challenges in predictive maintenance using AI and IoT: A comprehensive review. *Journal of Industrial Engineering and Management* 15(1), 35-47 (2022).